

Transparent Silicone Rubber

Description:

TX0 Series is Transparent Silicone Rubber available from 30 to 80 Hardness recommended for Extrusion & Molding Application. It can be used for Peroxide and Platinum Curing both.

Features:

Good Transparency Excellent Process-Ability Excellent Mechanical Properties Peroxide & Platinum Curable

Application:

Transparent Tubing's Extruded profiles Wire and Cable Transparent Molding



Product Data:

Item	T40	T50	Т60	T70	Т80
Appearance	Transparent				
Hardness	40	50	60	70	80
Tensile Strength [MPa]	8.00	8.00	9.00	9.00	8.50
Elongation, %	750	650	600	300	180
Tear Strength N/mm	25	26	30	25	22
Curing Agent	Molding - DBPMH 25% - 2 Parts, Extrusion – DCBP 50% Paste – 1.5phr				
Curing Condition	Molding - 1 st Cure - 170'C/5mins and Post Curing at 200'C/4hrs Extrusion – 1 st Cure – 120'C/5min and Post Curing at 200'C/4hrs				

Storage:

Store in Cool, Dry Place out of Direct Contact of Sunlight

Packing: 20kg Box

The Above Data is obtained from Testing and inspection of mentioned grade. The same has been found correct in accordance to the standard specification. Bhavik Enterprise is not liable for any loss or dispute arising from the use of the above information provided.

Importer & Stockist





We build relationships that build business

Address – D-720, 7^{tn} Floor, Neelkanth Business Park,

Vidhyavihar – West, Mumbai- 400086

Tel: 022-25092756, Extn: 207, Whats App- 9082849756

Email: <u>sales@berubber.com</u>
Web – www.berubber.com